

# LEDiving BASIC R5W



## Product family datasheet

### Technical data

Product description	Product information		General Product Information	Electrical Data	
	Application (Category and Product specific)	Product type (off-road vs. on-road)	Global order reference	Power input	Nominal voltage
LEDiving BASIC $\pm$ R5W	Mainly used for signal/ indicator applications	Off-road $\pm$ R5W	5107CW	0.96 W	12.0 V

Product description	Nominal wattage	Test voltage	Photometric Data		Physical Attributes & Dimensions
			Nominal luminous flux	Luminous flux tolerance	Diameter
LEDiving BASIC $\pm$ R5W	0 W	13.5 V	55 lm	$\pm$ 20 %	19.0 mm

Product description	Lifetime Data		Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
	Lifespan B3	Lifespan Tc	Technology	Primary article identifier	Candidate list substance 1
LEDiving BASIC $\pm$ R5W	2000 hr	2000 hr	LED	4052899463332   4052899414556   4052899463127   4052899414532	Lead

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDiving BASIC $\pm$ R5W	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	12c61241-8e84-49d2-aad6-61ee9185fc4c a74ed d59-fe84-466f-9e9c-d76036657cbc 4deab 8c0-c089-4d6a-90f4-3738f5af799e e8c7bd 92-d6cb-4cf2-9e8f-8360bae74918

## Product family datasheet

---

### Download Data

File	
	Brochures LEDriving Retrofits - Exchange overview (EN)

#### Legal advice

Not ECE conform Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

#### References / Links

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

