OSRAM

LEDriving BASIC R10W



Product family datasheet

Technical data

	Product in	nformation		General Product Information	Electrical [Electrical Data	
Product description		on (Category uct specific)	Product type (off- road vs. on-road)	Global order reference	Power input	Nominal voltage	
LEDriving BASIC ≜ R10W	signal/ in	Mainly used for signal/ indicator applications		5108CW	1.44 W	1.44 W 12.0 V	
				Photometric Data		Physical Attributes & Dimensions	
Product description	Nominal v	vattage	Test voltage	Nominal luminous flux	Luminous flux tolerance	Diameter	
LEDriving BASIC	1 W		13.5 V	85 lm	±20 %	19.0 mm	
	Lifetime [Lifetime Data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Product description	Lifespan B3	Lifespan Tc	Technology	Primary article identifier	Candidate substance		
LEDriving BASIC ≙ R10W	2000 hr	2000 hr	LED	4052899414570 4052899463141 4052899414594 4052899463356	Lead		

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC	7439-92-1	The identification of	1068a570-b34f-
		the Candidate List	446b-84ce-
		substance is	0f878db5b787 2115f
		sufficient to allow	bba-97ea-4065-
		safe use of the	9557-
		article.	f01077d71065 3d88a
			bbd-dd35-4bb0-
			bea6-
			4442158e669d b202
			dc8f-679a-4862-
			8048-9e2fbcf9ed99

Product family datasheet

Download Data

File



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

