Product family datasheet

OSRAM

LEDriving FL PSX24W





Cool White color temperature of 6,000 K

Better visibility in foggy situations with a perfect color match for xenon and LED headlights. Signs, obstacles and hazards can be recognized sooner.



More light allows to see farther and therefore react sooner with reduced glaring thanks to an optimized light distribution



Ultra compact LED replacement for conventional PSX24W fog lamps as socket solution Easy installation with optimized compatibility



New OSRAM LED fog lamps to increase safety and performance

The latest generation of OSRAM LED fog lamps provides an even more convenient solution in order to replace and upgrade existing halogen fog lamps with state-of-the-art LED technology. The color temperature of 6,000K provides for a stylish cool white look and improved visibility.

Product family datasheet

Technical data

	Product in	Product information		General Product Information	Electrical Data	
Product description		Application (Category and Product specific)		Global order reference	Nominal voltage	Nominal wattage
LEDriving FL \triangleq PSX24W	headlight/	Mainly used for headlight/ fog light applications		2604CW 12.0 V 6 W		6 W
				Data	Physical Attributes Dimensions	s & Lifetime Data
Product description	Test volta	Test voltage		Nominal lumino flux	us Diameter	Lifespan Tc
LEDriving FL \triangleq PSX24W	13.2 V		±20 %	730 lm	18.0 mm	5000 hr
		Capabilities	ilities Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Product description	Lifespan B3	Technology Primary identifie		ticle Declaration no. in SCIP database		
LEDriving FL \triangleq PSX24W	2500 hr	LED	40621720 40621720 40621724	58360	ete	

Product family datasheet

File

Download Data

7

Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.LEDriving CANBUS CONTROL UNIT (LEDCBCTRL102) avoids error messages on the board computer when using LED fog lights within 21 W applicationsRefer to www.osram.com/am-guarantee for precise conditions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.





1. 0 O

2. ⊂=[] ⇔ [







