## Product family datasheet

# LEDriving Curved Lightbar VX1000-CB SR SM



Single mount certified For individual installation



Up to 525 m long beam Improved view and visibility in low light conditions



**Combo beam** Designed for both: far-field and near-field illumination



OSRAM

Curved design Complements the vehicle's contours giving it a sleek and modern look

#### Illuminate your path with precision and style



Experience the ultimate lighting solution with our LEDriving Curved Lightbar VX1000-CB SR SM, specifically designed to provide both far-field and near-field illumination. With an impressive power level of 7650 effective lumens and 36 highperformance OSRAM LEDs, this lightbar ensures exceptional visibility up to 525 meters. The stylish curved design complements the contours of your vehicle, giving it a sleek and modern look. Even in dim light and reduced visibility due to external environmental influences, the OSRAM Curved Lightbar with up to 6000 Kelvin can provide conditions similar to daylight. In addition, it is certified for single mounting (2x ECE R149), offers the highest protection classes (IP6K8 & IP6K9K) and features a robust aluminum die-cast housing with a slim, single-row design. The included brackets allow for versatile mounting options on various parts of the vehicle, including curved surfaces like bumpers, grills, and windshields1). With a 2-year OSRAM guarantee2), this lightbar delivers proven quality and enhanced visibility at an economical price. Discover the perfect combination of performance, design, and versatility with our Curved Lightbar - ideal for those who value top quality and stylish design.

# Product family datasheet

### Technical data

	Product informationGeneral Product InformationdescriptionApplication (Category and Product specific)Global order reference		ct	Electrical Data			Photom etric Data
Product description				Nominal wattage Test voltage			Nominal luminou s flux
LEDriving Curved Lichtbar VX100-CB SR-SM	Driving Light - LEDDL135-CB SR 108 W 13.2 V Additional high beam application - central single mount					13.2 V	10100 lm
	Lifetime Data	Capabilities		ertificates & andards		cal data	
Product description	Lifespan Tc	Technology	ECE reference number		Commo	odity code	
LEDriving Curved Lichtbar VX100-CB SR-SM	> 5000 hr	LED	17.5 + 3	17.5	851220	00900	
	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)						
Product description	Declaration no. in						

LEDriving Curved Lichtbar VX100-CB In work SR-SM

SCIP database

Product family datasheet | LEDriving Curved Lightbar VX1000-CB SR SM © 2024, OSRAM GmbH. All rights reserved.

# Product family datasheet

#### Download Data

	File
*	User instruction LEDriving LEDDL135 Curved Lightbar VX1000-CB SR SM C

#### Safety advice

For detailed application information, please refer to the product data sheet and the user instruction

#### Legal advice

1) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.2) For precise conditions refer to: www.osram.com/am-guarantee

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.