## **OSRAM**

# BATTERYcharge 7PIN | PORTABLE | Type 2

Charging Cable for electric and plug-in hybrid vehicles





61016 Ampere

Variable charging currents of 6A/10A/16A meet individual charging requirements



1.32.23.6 kWh

Variable charging rates of 1.3/2.2/3.6 kWh meet individual charging requirements



5m cable length

Ergonomic handles for optimal handling and a cable length of 5 meters



Charge at home and on the move

Ergonomic handles for optimal handling and a cable length of 5 meters



#### Drive with OSRAM into a more emission-free future

Discover the world of electric driving with OSRAM. Charge your fully electric or plug in hybrid type 2 vehicle from any 32A (1 phase) charging unit or station fitted with a type 2 connection point. The charging cable is equipped with ergonomic handles for optimal handling and has a cable length of 5 meters. It is suitable for use at public charging stations and at home. In addition, the charging cables are equipped with dust protection caps and tested for water resistance according to IP65 and shock resistance according to IK10. Even when connected, the electrical contact points are protected against the ingress of dust and splash water in accordance with IP65 and IK10. The scope of delivery also includes a durable, compact storage bag to neatly store the cable after charging. In addition, the product is TÜV and CE certified and comes with a 2-year quarantee\*

## Product family datasheet

#### Technical data

	General Product Information	Electrical Data	Physical Attributes & Dimensions	
Product description	Global order reference	Nominal wattage	Nominal voltage	Length
BATTERY charge 7PIN   PORTABLE   Type 2 <sup>1)</sup>	OPC20A05	1300 W /2200 W /3600 W	240 V	5000 mm

			Lifetime Data	Certificates & standards
Product description	Width	Height	Guarantee	IK Class
BATTERY charge 7PIN   PORTABLE   Type 2 <sup>1)</sup>	120.0 mm	120.0 mm	2 years	IK10

	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
Product description	Candidate list substance 1	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database	
BATTERY charge 7PIN   PORTABLE   Type 2 <sup>1)</sup>	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	542fed56-27b1- 425b-a4a9- 2a4fce914aac	

<sup>1)</sup> Nominal current 6 A/10 A/16 A

### Product family datasheet

#### Legal advice

Application advice: For more detailed application information and graphics please see product datasheet and the user instruction.\* for precise conditions please refer to:

www.osram.com/am-guarantee

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.